

EVOLÍA Series

Permanent Magnet VFD Driven
Multi-Staged Self Priming
Centrifugal Pump





EVOLÍA is a permanent magnet frequency converted multi-stage self priming centrifugal pump.

- **Super Silent:** Unique fluid noise reduction technology, efficient and silent permanent magnet motor technology, greatly reduce the working noise of the pump to a minimum 30-50 decibels.
- **Convenient Disassembly:** Without the need to disassemble the pipeline, the four screws on the casing can be removed for maintenance and repair.
- **Multiple Protections:** IP55 protection level ensures the safe operation of the water pump outdoors, including leakage warning, water shortage protection, voltage protection and temperature control provide users with a safer and more reliable water experience.




LOW
NOISE
SUPER-CHARGE

High efficiency,
low noise

ENERGY
SAVING AND
ENVIRONMENTAL
PROTECTION

Energy and power saving,
excellent and efficient

CURVE DIAGRAM & TECHNICAL PARAMETERS



30
db

The sound
of flowers
blooming

50
db

Running
sound of
EVOLIA

60
db

Normal
conversation

70
db

The sound
of the
range hood

Model	EVOLÍA 370	EVOLÍA 550	EVOLÍA 750	EVOLÍA 900	EVOLÍA 1100
Voltage	165-260V	165-260V	165-260V	165-260V	165-260V
Frequency	50/60Hz	50/60Hz	50/60Hz	50/60Hz	50/60Hz
Power	370W	550W	750W	900W	1100W
Water Temperature Range	0-75°C	0-75°C	0-75°C	0-75°C	0-75°C
Ambient Temperature	0-50°C	0-50°C	0-50°C	0-50°C	0-50°C
Pressure adjustment Range	1.5-4.5 bar	1.5-5 bar	1.5-5.5 bar	1.5-6.0 bar	1.5-6.0 bar
Max. Flow	4.0 m³/h	5.2 m³/h	5.6 m³/h	6.0 m³/h	12 m³/h
Max. Lift	32 m	48 m	55 m	60 m	60 m
Rated Flow	1.8 m³/h	3.0 m³/h	3.0 m³/h	3.0 m³/h	6.0 m³/h
Rated Lift	20 m	24 m	30 m	38 m	30 m
Max. Suction	8 m	8 m	8 m	8 m	8 m

CURVE DIAGRAM & TECHNICAL PARAMETERS



Model	Power		Q	m³/h	0	0.6	1.2	1.8	2.4	3.0	3.6	4.2	4.8	5.4	6.0
	KW	HP		l/min	0	10	20	30	40	50	60	70	80	90	100
EVOLÍA 370	0.37	0.5	H (m)		32	29	26	23	19	12	10				
EVOLÍA 550	0.55	0.75			48	44	39	33	28	24	18	13	5		
EVOLÍA 750	0.75	1.0			55	52	48	42	36	28	23	17	8	3	
EVOLÍA 900	0.9	1.2			60	60	55	52	48	38	31	26	22	10	3

Model	Power		Q	m³/h	0	1.2	2.4	3.6	4.8	6.0	7.2	8.4	9.6	10.8	12
	KW	HP		l/min	0	20	40	60	80	100	120	140	160	180	200
EVOLÍA 1100	1.1	1.5	H (m)		60	55	48	39	35	28	22	18	13	8	3

EVOLÍA Series



CONSTRUCTION

- Multi-stage, centrifugal, permanent magnet driven motor, variable speed pump with a plug and play solution
- Pump body made of thickened stainless steel material which is corrosion resistant
- Microcomputer control system automatically detect and control the motor to keep always constant pressure by changing frequency

APPLICATIONS

- For water supply systems domestic and commercial use for garden and irrigation

FEATURES

- Integrated frequency converter
- Built-in pressure vessel
- High efficiency permanent magnet driven motor
- Motor power / voltage control
- Programmable menu
- Monitoring pressure and current

MATERIALS

- Stainless steel pump body, PPO impeller, carbon-ceramic- NBR mechanical seal

PROTECTIONS

- Dry run protection
- Overland control and overheating motor control
- Power supply control
- Pump clogage prevention
- Stop delay function
- Detects small leakages in system


OPERATING CONDITIONS

- Liquid temperature: 0°C to 75°C
- Ambient temperature: 50°C
- Max. casing temperature: 10 bar
- Suction lift: up to 8m


MOTOR

- Variable speed motor
- Max. speed: 5200 rpm
- Frequency: 50 Hz / 60 Hz
- Voltage: 165 – 260 V
- Insulation class: F
- Protection: IPX5
- Constructed in accordance with EN60034-1; EN60335-1, EN60335-2-41


EVOLÍA Series




MENU USE



PRESSURE SETTING



MODE OF OPERATION



EVOLÍA Series



MODE SWITCH

Press  key 10s, Switch to rev mode.
In constant voltage mode  lights on,
In manual cycle mode  extinguished.

Remarks: 1. In speed mode, the water pump screen displays the current running speed of the water pump.
2. In this mode, the water pump will not stop.
Only when the pressure sensor or controller fails, this mode can ensure that the water pump temporarily uses water.




 Increase pump speed
 Decrease pump speed


RESET

Press  key 3s, All parameters are restored to factory settings.

USE MENU



EVOLÍA Series



DIRECTIONS FOR USE



! In 2-pumps installation, pressure should be set up consistently in terms of master/slave configuration



Enter the online features:

Pick 1 pumps as a host, long press the button 3 s, into the online setting pattern, the electricity run indicator in the flashing state, on behalf of the online success.

Exit the online features:

Long press the button 3 s host panel, the red light to stop flashing, representatives have withdrawn from the online mode.

Operation mode:

A. when the host running 0.2 bar pressure below the set pressure, the no. 2 machine automatic startup, automatically adjust the pressure to the set pressure value.

B. when the tap all closed, the pump stop running; To open the faucet, no. 2 machine start, when the machine run 2 pressure below the set pressure is 0.2 bar, the host start automatically.

C. 2 pumps used interchangeably, service life is the same, when one pump fails, automatic exit online function.

EVOLÍA Series



EXPLOSION CHART



POS	PART	POS	PART
1	Hull	14	Fan cover
2	Water inlet Guide glade	15	Fan
3	Guide glade	16	Capacitor box
4	Impeller	17	Gland
5	Prop	18	Controller
6	Radiation fin	19	Stator
7	Seal holder	20	Overhead tank
8	Pump support	21	Transducer
9	Motherboard	22	Sensor bracket
10	Water proof gland	23	Bottom bracket
11	Rotor	24	Check valve
12	Bearing	25	Pump body
13	Spring Washer	26	Check valve



DIMENSIONAL DRAWINGS



Model	DN1	DN2	L (mm)	L1 (mm)	W (mm)	W1 (mm)	H (mm)	H1 (mm)	D
EVOLÍA 370 & EVOLÍA 550	1"	1"	360	61	184	171	290	95	12
EVOLÍA 750 & EVOLÍA 900	1"	1"	400	64	204	190	320	110	12
EVOLÍA 1100	1-1/4"	1-1/4"	436	107	204	190	320	110	12



EBITT EUROPE KFT

H-6782 Mórahalom, Szegedi út 108. Hungary Phone: +3662-280-926

Fax: +3662-280-927

export@ebitteurope.com

www.ebitt-europe.com



EBITTME PUMPS ENGINES VALVES & SPARE PARTS TRADING CO. L.L.C.

ALSUAIDI, Al Suwaidi Bldg, Al Murar - Deira

P.O. Box 453929 Dubai, UAE

emea@ebitteurope.com

+971 55-454 4187



EBITT FINDUSTRIE (ZHE JIANG) INDUSTRIAL ENGINEERING LIMITED COMPANY

Hangzhou City, Zhejiang Province, China

info@ebitt.com.cn

+86 15168651662

EBITT ASIA PACIFIC PTE LTD (EAP Singapore)

226 Jalan Eunos #04-128. Singapore 415869 Phone: (65) 98393745

info@ebitt-asiapac.com

EBITT TÜRKİYE

Koçullu Mah. Doğru Sok. No:6 34799 Çekmeköy / İstanbul

info@ebitt.com.tr

www.ebitt.com.tr